

Архангельск (8182)63-90-72	Ижевск (3412)26-03-58	Магнитогорск (3519)55-03-13	Пермь (342)205-81-47	Сургут (3462)77-98-35
Астана (7172)727-132	Иркутск (395)279-98-46	Москва (495)268-04-70	Ростов-на-Дону (863)308-18-15	Тверь (4822)63-31-35
Астрахань (8512)99-46-04	Казань (843)206-01-48	Мурманск (8152)59-64-93	Рязань (4912)46-61-64	Томск (3822)98-41-53
Барнаул (3852)73-04-60	Калининград (4012)72-03-81	Набережные Челны (8552)20-53-41	Самара (846)206-03-16	Тула (4872)74-02-29
Белгород (4722)40-23-64	Калуга (4842)92-23-67	Нижний Новгород (831)429-08-12	Санкт-Петербург (812)309-46-40	Тюмень (3452)66-21-18
Брянск (4832)59-03-52	Кемерово (3842)65-04-62	Новокузнецк (3843)20-46-81	Саратов (845)249-38-78	Ульяновск (8422)24-23-59
Владивосток (423)249-28-31	Киров (8332)68-02-04	Новосибирск (383)227-86-73	Севастополь (8692)22-31-93	Уфа (347)229-48-12
Волгоград (844)278-03-48	Краснодар (861)203-40-90	Омск (3812)21-46-40	Симферополь (3652)67-13-56	Хабаровск (4212)92-98-04
Вологда (8172)26-41-59	Красноярск (391)204-63-61	Орел (4862)44-53-42	Смоленск (4812)29-41-54	Челябинск (351)202-03-61
Воронеж (473)204-51-73	Курск (4712)77-13-04	Оренбург (3532)37-68-04	Сочи (862)225-72-31	Череповец (8202)49-02-64
Екатеринбург (343)384-55-89	Липецк (4742)52-20-81	Пенза (8412)22-31-16	Ставрополь (8652)20-65-13	Ярославль (4852)69-52-93
Иваново (4932)77-34-06	Киргизия (996)312-96-26-47	Россия (495)268-04-70	Казахстан (772)734-952-31	

Адрес сайта: www.gwinstek.nt-rt.ru || эл. почта: gnw@nt-rt.ru



Технические характеристики на генераторы специальной формы AFG-200 и AFG-100

Модели:	AFG-200 и AFG-100.
----------------	--------------------

USB MODULAR ARBITRARY FUNCTION GENERATOR

AFG-125/125P/225/225P



NEW



The brand new AFG-100/200 Series USB modular arbitrary function generator has four models for selections. The AFG-100/200 Series arbitrary function generator with many unique features such as light weight, handy, and USB interface compatible is an ideal choice for the applications at the general laboratories in applying stand-alone operation or collocation with the GDS-2000A Series digital oscilloscope.

The model, channel, and power arrangements of the AFG-100/200 Series are as follows:

	AFG-125	AFG-125P	AFG-225	AFG-225P
Channels	1	1	2	2
DC Power	NA	Yes	NA	Yes

DC power selections include 2.5V, 3.3V, and 5V.

One external 5V power supply (optional GPA-501) and PC software are required to independently operate the AFG-100/200 Series. When the AFG-100/200 Series is collocating with the GDS-2000A Series digital oscilloscope, the USB port of the GDS-2000A Series will provide the AFG-100/200 Series with necessary power.

The main features of the AFG-100/200 Series are output amplitude of 2.5Vpp (connecting with a load of 50 ohms), frequency range reaching 25MHz, frequency resolution of 1μ Hz, and built-in sine waveform, square waveform, triangle waveform, and noise signal. Square waveform can adjust the duty cycle from 1% to 99% and it can be utilized as pulse signal. Users, via the GDS-2000A APP, can select from the 66 built-in function waveforms to conduct arbitrary waveform editing. The AFG-100/200 Series, with functions of AM/FM/PM/FSK/SUM modulation, frequency sweep, burst and coupling, is suitable for various communications applications.

The AFG-100/200 Series provides arbitrary waveform sampling rate of 120 MSa/s, 10 bit resolution and arbitrary waveform editing function with 4k point memory to produce true point-by-point arbitrary waveform output. The easy-to-use external software interface allows users to quickly and conveniently operate the AFG-100/200 Series.

The AFG-100/200 Series connects the GDS-2000A series digital oscilloscope through the USB interface to directly duplicate and produce the retrieved waveform signals. Users can edit the required waveforms by the external computer software and send the edited waveforms to the AFG-100/200 Series to produce signals. The external computer program supports importing CSV format files.

AFG-225/225P dual channel models support independent channel or related channel applications. Three related functions are coupling, tracking and phase.

- * The coupling function allows users to freely set ratio and offset values for frequency and amplitude of both channels to realize that all parameters are simultaneously effective for both channels. The measurement of the Third-Order Intercept Point for an amplifier and the simulations of two different frequency oscillators outputting signals are two application examples for the coupling function.
- * The tracking function can produce 180 degree phase offset differential signals with same frequency and amplitude.
- * The phase function allows users to freely set phase parameters for both channels such as sine and cosine waveform signals.

The sum modulation function can sum up two signals into one and output this signal via one channel. One of the related applications is to sum up sine waveform and noise to execute speaker distortion tests.

FEATURES

- Output Amplitude Range From 1mVpp to 2.5Vpp (into 50Ω)
- Wide Frequency Ranges From 1μ Hz ~ 25MHz (sine wave)
- 1μ Hz Resolution in Full Range
- Built-in Standard 120MSa/s, 10bit, 4k Points Arbitrary Function for Both Channels
- True Dual-Channel Output, CH2 Provides the Same Characteristics as CH1
- Dual-Channel Supports Couple, Tracking, Phase Operations
- 1% ~ 99% Adjustable Duty Cycle for Square Waveform
- Friendly User Interface for Easy Parameter Setting and Parameters Display
- Multiple Editing Methods to Edit Arbitrary Waveform Easily
- Built-in Standard AM/FM/PM/FSK/SUM/Sweep/Burst
- USB Device Interface for Remote Control and Waveform Editing



AFG-125



AFG-125P



AFG-225



AFG-225P

APPLICATIONS

- Power Supply / Transformer Simulations
- Laboratory and Educational Research
- Pulse Signal as Trigger or Synchronization
- Audio Electronics Applications
- Analog Circuit Testing

AFG-100/200 Series

GW INSTEK
Simply Reliable

S		AFG-125/AFG-125P	AFG-225/AFG-225P
MODEL		1	2
OUTPUT CHANNELS WAVEFORMS		Sine, Square, Ramp, Pulse, Noise, ARB	
ARBITRARY FUNCTIONS	Sample Rate Repetition Rate Waveform Length Amplitude Resolution Non-Volatile Memory	120 MSa/s 60MHz 4k points 10 bits 4k points	
FREQUENCY CHARACTERISTICS	Range Ramp Resolution Accuracy	Sine/Square 1μHz~25MHz 1μHz~1MHz 1μHz ±20 ppm ±1 ppm, per 1 year ≤1 mHz	
OUTPUT CHARACTERISTICS	Amplitude Offset	Range Accuracy Resolution Flatness Units Range	GPA-501 power supply: 1mVpp ~ 2.5Vpp (into 50Ω), 2mVpp ~ 5Vpp (open-circuit) USB power supply : 1mVpp ~ 2Vpp (into 50Ω), 2mVpp ~ 4Vpp (open-circuit) ±2% of setting ±1 mVpp (at 1 kHz) 1mV or 3 digits ±1%(0.1dB) ≤100kHz, ±3%(0.3 dB) ≤5MHz, ±5%(0.4 dB) ≤12MHz, ±10%(0.9dB) ≤25MHz (sine wave relative to 1kHz) Vpp, Vrms, dBm GPA-501 power supply: ±1.25 Vpk ac +dc (into 50Ω), ±2.5Vpk ac +dc (Open circuit) USB power supply: ±1 Vpk ac +dc (into 50Ω), ±2 Vpk ac +dc (Open circuit) 2% of setting + 10mV+ 0.5% of amplitude
WAVEFORM OUTPUT	Impedance Protection		50Ω typical (fixed), > 10MΩ (output disabled) Short-circuit protected. Overload relay automatically disables main output
SINE WAVE CHARACTERISTICS	Harmonic Distortion		≤-50 dBc DC ~ 1MHz, Ampl >1Vpp ≤-35 dBc 1MHz ~ 5MHz, Ampl >1Vpp ; ≤-30 dBc 5MHz ~ 25MHz, Ampl > 1Vpp
SQUARE WAVE CHARACTERISTICS	Rise/Fall Time Overshoot Asymmetry Variable duty Cycle		≤10ns at maximum output. (into 50 Ω load) <2% 1% of period +5 ns 1.0% ~ 99.0% ≤100kHz; 10% to 90% ≤ 1MHz, 50% ≤ 25MHz
RAMP CHARACTERISTICS	Linearity Variable Symmetry		<0.1% of peak output 0% to 100% (0.1% Resolution)
PULSE CHARACTERISTICS	Period Pulse Width Overshoot Accuracy Jitter		40ns ~ 2000s 20ns ~ 1999.9s <2% 0.1%+20ns 20ppm +10ns
AM MODULATION	Carrier Waveforms Modulating Waveforms Modulating Frequency Depth Source		Sine, Square, Ramp, Pulse, Arb Sine, Square, Triangle, Upramp, Dnramp 2mHz ~ 20kHz 0% ~ 120.0% Internal
FM MODULATION	Carrier Waveforms Modulating Waveforms Modulating Frequency Peak Deviation Source		Sine, Square, Ramp, Sine, Square, Triangle, Upramp, Dnramp 2mHz ~ 20kHz DC to Max Frequency Internal
SWEEP	Waveforms Type Start/Stop Freq Sweep Time Source		Sine, Square, Ramp, Linear or Logarithmic 1μHz to Max Frequency 1ms ~ 500s Internal / Manual
FSK	Carrier Waveforms Modulating Waveforms Modulation Rate Frequency Range Source		Sine, Square, Ramp, Pulse 50% duty cycle square 2mHz ~ 100 kHz 1μHz to Max Frequency Internal
PM	Carrier Waveforms Modulating Waveforms Modulation Frequency Phase deviation Source		Sine, Square, Ramp Sine, Square, Triangle, Upramp, Dnramp 2mHz ~ 20kHz 0° ~ 360° Internal
SUM	Carrier Waveforms Modulating Waveforms Modulation Frequency SUM Depth Source		Sine, Square, Ramp, Pulse, Noise Sine, Square, Triangle, Upramp, Dnramp 2mHz to 20kHz 0% ~ 100.0% Internal
SYNC OUTPUT	Type Level Assignment Polarity Fan-out Impedance		Sync, Sweep Marker, Burst Marker or Arbitrary Waveform Marker TTL Compatible into 50Ω Channel 1 or Channel 2 Normal or Inverted ≥4 TTL Load 50Ω Typical
DUAL CHANNEL FUNCTION	Phase Track Coupling		-180° ~180° (Square and Pulse can not be change, Phase is 0°), Synchronize phase CH2=CH1 OR CH1=CH2 Frequency(Ratio or Difference), Amplitude & DC Offset
BURST	Waveforms Frequency Burst Count Start/Stop Phase Internal Period Gate Source Trigger Source		Sine, Square, Ramp, Arb 1uHz~15 MHz(sine), 1uHz~15 MHz(Square), 1uHz~1 MHz (Ramp) 1 ~ 65535 cycles or Infinite -360 ~ +360 1ms ~ 500s External Trigger Single or Internal Rate
TRIGGER DELAY	N-Cycle, Infinite		0s to 655350ns
SAVE RECALL			10 Groups of Setting Memories
POWER OUTPUT	Only AFG-125P/AFG-225P		Output Voltage : (2.5V/3.3V/5V)±5%, Output Current : 0.6A
INTERFACE	Power Source Power Consumption Operating Environment		USB (Device) DC 5V 10 W (Max)
GENERAL SPECIFICATIONS	Operating Altitude Storage Temperature		Temperature to satisfy the specification : 18 ~ 28°C , Operating temperature : 0 ~ 40°C Relative Humidity : < 80%, 0 ~ 40°C, Installation category : CAT II 2000 Meters -10~70°C, Humidity : ≤ 70%
DIMENSIONS & WEIGHT			215 (W) x 35 (H) x 107(D) mm, Approx. 1kg

Архангельск (8182)63-90-72	Ижевск (3412)26-03-58	Магнитогорск (3519)55-03-13	Пермь (342)205-81-47	Сургут (3462)77-98-35
Астана (7172)727-132	Иркутск (395)279-98-46	Москва (495)268-04-70	Ростов-на-Дону (863)308-18-15	Тверь (4822)63-31-35
Астрахань (8512)99-46-04	Казань (843)206-01-48	Мурманск (8152)59-64-93	Рязань (4912)46-61-64	Томск (3822)98-41-53
Барнаул (3852)73-04-60	Калининград (4012)72-03-81	Набережные Челны (8552)20-53-41	Самара (846)206-03-16	Тула (4872)74-02-29
Белгород (4722)40-23-64	Калуга (4842)92-23-67	Нижний Новгород (831)429-08-12	Санкт-Петербург (812)309-46-40	Тюмень (3452)66-21-18
Брянск (4832)59-03-52	Кемерово (3842)65-04-62	Новокузнецк (3843)20-46-81	Саратов (845)249-38-78	Ульяновск (8422)24-23-59
Владивосток (423)249-28-31	Киров (8332)68-02-04	Новосибирск (383)227-86-73	Севастополь (8692)22-31-93	Уфа (347)229-48-12
Волгоград (844)278-03-48	Краснодар (861)203-40-90	Омск (3812)21-46-40	Симферополь (3652)67-13-56	Хабаровск (4212)92-98-04
Вологда (8172)26-41-59	Красноярск (391)204-63-61	Орел (4862)44-53-42	Смоленск (4812)29-41-54	Челябинск (351)202-03-61
Воронеж (473)204-51-73	Курск (4712)77-13-04	Оренбург (3532)37-68-04	Сочи (862)225-72-31	Череповец (8202)49-02-64
Екатеринбург (343)384-55-89	Липецк (4742)52-20-81	Пенза (8412)22-31-16	Ставрополь (8652)20-65-13	Ярославль (4852)69-52-93
Иваново (4932)77-34-06	Киргизия (996)312-96-26-47	Россия (495)268-04-70	Казахстан (772)734-952-31	

Адрес сайта: www.gwinstek.nt-rt.ru || эл. почта: gnw@nt-rt.ru